

572 PROLIFLEX HP - 572



SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

**SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

**1.1. Product identifier**

Product name : 572 PROLIFLEX HP

Product code : 572.

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Construction, ready-to-wet mortar

Refer to the technical data sheet

Tile adhesive.

**1.3. Details of the supplier of the safety data sheet**

Registered company name : PAREXGROUP S.A.

Address : 19, place de la résistance - CS 50053.92445.Issy les Moulineaux Cedex.France.

Telephone : (33)01.41.17.20.00. Fax : 01.41.17.21.30.

fds.matiere-fr@parex-group.com

www.parexlanko.com

For UK : Emergency telephone number : 01827 711755 (Mon - Fri 08:30 - 16:30).

**1.4. Emergency telephone number : +33 (0)1 45 42 59 59.**

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

**SECTION 2 : HAZARDS IDENTIFICATION**

**2.1. Classification of the substance or mixture**

**In compliance with EC regulation No. 1272/2008 and its amendments.**

Skin irritation, Category 2 (Skin Irrit. 2, H315).

Serious eye damage, Category 1 (Eye Dam. 1, H318).

Skin sensitisation, Category 1 (Skin Sens. 1, H317).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H335).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

**2.2. Label elements**

**In compliance with EC regulation No. 1272/2008 and its amendments.**

Hazard pictograms :



GHS05



GHS07

Signal Word :

DANGER

Product identifiers :

EC 266-043-4

PORTLAND CEMENT CLINKER

EC 270-659-9

FLUE DUST, PORTLAND CEMENT

Hazard statements :

H315

Causes skin irritation.

H317

May cause an allergic skin reaction.

**572 PROLIFLEX HP - 572**

H318	Causes serious eye damage.
H335	May cause respiratory irritation.
Precautionary statements - General :	
P102	Keep out of reach of children.
Precautionary statements - Prevention :	
P261	Avoid breathing dust.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary statements - Response :	
P302 + P352	IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or a doctor.
Precautionary statements - Disposal :	
P501	To eliminate the contents / packaging in a waste collection point. Beforehand, the product should be inerted by hardening in the water and the packagings should be completely emptied.

**2.3. Other hazards**

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq 0.1\%$  published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

**SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**

**3.2. Mixtures**

**Composition :**

Identification	(EC) 1272/2008	Note	%
INDEX: 2076 CAS: 14808-60-7 EC: 238-878-4 REACH: EXEMPTÉ		[1]	50 $\leq$ x % < 100
QUARTZ			
INDEX: 2999 CAS: 65997-15-1 EC: 266-043-4 REACH: EXEMPTÉ	GHS07, GHS05 Dgr Skin Irrit. 2, H315 Skin Sens. 1B, H317 Eye Dam. 1, H318 STOT SE 3, H335	[1]	25 $\leq$ x % < 50
PORTLAND CEMENT CLINKER			
INDEX: 2821 CAS: 68475-76-3 EC: 270-659-9 REACH: 01-2119486767-17-0003	GHS07, GHS05 Dgr Skin Irrit. 2, H315 Skin Sens. 1B, H317 Eye Dam. 1, H318 STOT SE 3, H335		1 $\leq$ x % < 2.5
FLUE DUST, PORTLAND CEMENT			

(Full text of H-phrases: see section 16)

**Information on ingredients :**

[1] Substance for which maximum workplace exposure limits are available.

**SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

---

**572 PROLIFLEX HP - 572**

---

**4.1. Description of first aid measures**

**In the event of exposure by inhalation :**

In the event of massive inhalation of dust, remove the person exposed to fresh air. Keep warm and at rest.

Wash nose and throat with water (only if the victim is conscious). Remove the person outdoors to fresh air. In case of respiration trouble, consult a doctor.

**In the event of splashes or contact with eyes :**

Rinse IMMEDIATELY with a large amount of water for at least 15 minutes holding the eyelids open. Consult immediately an eye doctor.

**In the event of splashes or contact with skin :**

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

For dry powder, eliminate the dust and wash copiously with water. For wet powder, wash with a large amount of water.

**In the event of swallowing :**

For small quantities, rinse the mouth with water and seek medical advice. For large quantities, do not allow the person to drink, do not cause the person to vomit. Transfer the person to a hospital and show the product label or this material safety data sheet to the medical staff on duty.

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed**

**Specific and immediate treatment :**

Wash copiously with water.

---

**SECTION 5 : FIREFIGHTING MEASURES**

Non-flammable.

**5.1. Extinguishing media**

No data available.

**5.2. Special hazards arising from the substance or mixture**

**5.3. Advice for firefighters**

No data available.

---

**SECTION 6 : ACCIDENTAL RELEASE MEASURES**

**6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

**For non first aid worker**

Avoid contact with eyes and skin and breathing dust. Use the product with suitable working clothes (goggles, working-suit, boots,...) and wear a dust mask in case of dust in air.

**For first aid worker**

First aid workers will be equipped with suitable personal protective equipment (See section 8).

**6.2. Environmental precautions**

Prevent any material from entering drains or waterways.

Use drums to dispose of waste recovered in accordance with applicable regulations (see heading 13).

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

**6.3. Methods and material for containment and cleaning up**

Collect product by machine and transfer to suitable container.

After setting, the product can be disposed of as an usual construction waste.

**6.4. Reference to other sections**

No data available.

**572 PROLIFLEX HP - 572**

**SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.  
Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

**7.1. Precautions for safe handling**

Always wash hands after handling.  
Remove and wash contaminated clothing before re-using.  
The product should be handled in well-ventilated areas. Avoid the creation of dust. In case of airborne dust, use a powder mask.

**Recommended equipment and procedures :**

For personal protection, see section 8.  
Observe precautions stated on label and also industrial safety regulations.  
Avoid inhaling dust.  
Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.  
Avoid eye contact with this mixture at all times.

**Prohibited equipment and procedures :**

No smoking, eating or drinking in areas where the mixture is used.  
Never open the packages under pressure.

**7.2. Conditions for safe storage, including any incompatibilities**

No data available.

**Storage**

Keep out of reach of children.  
In dry conditions.

**Packaging**

Always keep in packaging made of an identical material to the original.

**7.3. Specific end use(s)**

No data available.

**SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1. Control parameters**

**Occupational exposure limits :**

- Germany - AGW (BAuA - TRGS 900, 29/01/2018) :

CAS	VME :	VME :	Excess	Notes
65997-15-1	-	5 mg/m3 E	-	DFG

- Belgium (Arrêté du 09/03/2014, 2014) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
14808-60-7	0,1 mg/m <sup>3</sup>				
65997-15-1	10 mg/m <sup>3</sup>				

- France (INRS - ED984 :2016) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
14808-60-7	-	0.1 A	-	-	-	25

- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
14808-60-7	0.3 mg/m3	-	-	-	R
65997-15-1	- ppm 4 mg/m <sup>3</sup>	- ppm - mg/m <sup>3</sup>			

**Derived no effect level (DNEL) or derived minimum effect level (DMEL):**

PORTLAND CEMENT CLINKER (CAS: 65997-15-1)

**Final use:**

Exposure method:  
Potential health effects:

**Workers.**

Inhalation.  
Short term local effects.

**572 PROLIFLEX HP - 572**

DNEL :

3 mg of substance/m<sup>3</sup>

**8.2. Exposure controls**

**Appropriate engineering controls**

Avoid contact with mucous membranes, eyes and hands.

Do not rub the eyes with dirty hands.

Anyone with a history of skin sensitisation must on no account handle such products.

**Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

**- Eye / face protection**

Avoid contact with eyes.

Before handling powders or dust emission, wear mask goggles in accordance with standard EN166.

Prescription glasses are not considered as protection.

Envisage in the vicinity a clean water container or an ocular fountain in the event of projection in the eyes

In case of powder or paste splashing risk, use protective glasses goggles.

**- Hand protection**

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Waterproof work gloves or creams.

Waterproof neoprene or nitrile protective gloves lined with cotton or jersey (in accordance with EN 374).

**- Body protection**

Avoid skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

Closed working clothes protecting forearms in continuous with gloves. In case of kneeling work, waterproof kneepads are recommended. Protective "barrier" creams can be used. Avoid prolonged contact. Ensure that no product remains between the skin and the clothes, the watch, the shoes.

**- Respiratory protection**

Avoid breathing dust.

Type of FFP mask :

Wear a disposable half-mask dust filter in accordance with standard EN149.

Category :

- FFP2

Powder mask in case of airborne dust.

**- Thermal risks**

The substance shows no thermal hazard.

---

**SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**

**9.1. Information on basic physical and chemical properties**

**General information :**

Physical state :

Powder or dust.

**Important health, safety and environmental information**

pH :

Not stated.

Strongly basic.

Boiling point/boiling range :

Not relevant.

Flash point interval :

Not relevant.

Vapour pressure (50°C) :

Not relevant.

**572 PROLIFLEX HP - 572**

Density :	> 1
Water solubility :	Dilutable.
Melting point/melting range :	Not relevant.
Self-ignition temperature :	Not relevant.
Decomposition point/decomposition range :	Not relevant.

**9.2. Other information**

No data available.

---

**SECTION 10 : STABILITY AND REACTIVITY**

**10.1. Reactivity**

No data available.

**10.2. Chemical stability**

This mixture is stable under the recommended handling and storage conditions in section 7.

**10.3. Possibility of hazardous reactions**

No data available.

**10.4. Conditions to avoid**

Avoid :

- humidity

The mortar can harden in humid conditions.

**10.5. Incompatible materials**

No data available.

**10.6. Hazardous decomposition products**

No data available.

---

**SECTION 11 : TOXICOLOGICAL INFORMATION**

**11.1. Information on toxicological effects**

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

May have irreversible effects on the eyes, such as tissue damage in the eye, or serious physical decay of sight, which is not fully reversible by the end of observation at 21 days.

Serious eye damage is typified by the destruction of cornea, persistent corneal opacity and iritis.

Respiratory tract irritation may occur, together with symptoms such as coughing, choking and breathing difficulties.

May cause an allergic reaction by skin contact.

**11.1.1. Substances**

**Acute toxicity :**

PORTLAND CEMENT CLINKER (CAS: 65997-15-1)

Dermal route : LD50 > 2000 mg/kg  
Species : Rabbit

QUARTZ (CAS: 14808-60-7)

Oral route : LD50 > 2000 mg/kg

Dermal route : LD50 > 2000 mg/kg

**Serious damage to eyes/eye irritation :**

PORTLAND CEMENT CLINKER (CAS: 65997-15-1)

Corneal haze : Average score = 128

**11.1.2. Mixture**

**Skin corrosion/skin irritation :**

In case of damp skin, the partial hydration of cement increases the pH and can irritate the skin. A prolonged contact with a cement paste can induce skin burning.

---

**572 PROLIFLEX HP - 572**

---

**Serious damage to eyes/eye irritation :**

The cement can induce eyelids irritation (blepharitis), corneal irritation (conjunctivitis) and create eyeball injury.

**Respiratory or skin sensitisation :**

The cement can induce irritation of the respiratory tract and a nasal mucous inflammation. In extreme case, mucous erosion has been observed.

Prolonged exposure without proper protection (gloves) can cause skin irritation (fissural dermatitis). In subjects prone to allergies, these lesions may precede an allergy to certain elements present in trace amounts in the cement. Other lesions may be encountered with unprotected prolonged contact. They usually appear on fingers fissural dermatitis, ulcers, kyperkératoses.

May cause an allergic skin reaction.

**Other information**

If significant swallowed, cement is caustic for the digestive tract, it may cause burns of the mouth, oesophagus and stomach.

---

**SECTION 12 : ECOLOGICAL INFORMATION**

**12.1. Toxicity**

**12.1.2. Mixtures**

The product must not be allowed to run into drains or waterways.

**12.2. Persistence and degradability**

No data available.

**12.3. Bioaccumulative potential**

none.

**12.4. Mobility in soil**

none.

**12.5. Results of PBT and vPvB assessment**

No data available.

**12.6. Other adverse effects**

In case of accidental pouring in waste water, the product causes a low pH rise . Cement is a stable material that permanently fixes its compounds and makes them insoluble.

---

**SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

**13.1. Waste treatment methods**

Do not pour into drains or waterways.

After curing, the mortar can be removed like other construction debris and stored in landfills in accordance with appropriate regulations.

**Waste :**

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

**Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :**

17 01 01 concrete

---

**SECTION 14 : TRANSPORT INFORMATION**

Exempt from transport classification and labelling.

**14.1. UN number**

-

**14.2. UN proper shipping name**

-

**572 PROLIFLEX HP - 572**

**14.3. Transport hazard class(es)**

-

**14.4. Packing group**

-

**14.5. Environmental hazards**

-

**14.6. Special precautions for user**

-

**SECTION 15 : REGULATORY INFORMATION**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**- Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2018/1480 (ATP 13)
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2019/521 (ATP 12)

**- Container information:**

No data available.

**- Particular provisions :**

No data available.

**- Standardised American system for the identification of hazards presented by the product in view of emergency procedures (NFPA 704) :**

NFPA 704, Labelling: Health=3 Inflammability=1 Instability/Reactivity=1 Specific Risk=none



**15.2. Chemical safety assessment**

No data available.

**SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

**Wording of the phrases mentioned in section 3 :**

- |      |                                      |
|------|--------------------------------------|
| H315 | Causes skin irritation.              |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage.           |
| H335 | May cause respiratory irritation.    |

**Abbreviations :**

DNEL : Derived No-Effect Level

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

GHS05 : Corrosion



---

**572 PROLIFLEX HP - 572**

---

GHS07 : Exclamation mark

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.